


5		4		3		2		1	
<p>NOTES:</p> <p>1. MATERIAL: RUBBER COMPOSITION, MIL-STD-417: TYPE S, CLASS SB, GRADE 715, SUFFIX A, B, E3, F2. COLOR: BLACK 37038 OF FED. STD 595.</p> <p>2. ON ALL EDGES, .01 RADII PERMISSIBLE.</p>						REVISIONS			
						LTR	DESCRIPTION	DATE	APPROVED
							REPLACES WITH CHANGE DWG 11010048 DATED 8 APR 66, SEE EO SA 28943		<i>R. S. Henry</i>
									
PART NO. 11686524						U. S. ARMY SPRINGFIELD ARMORY SPRINGFIELD, MASS. 01101			
MECHANICAL PROPERTIES		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		ORIGINAL DATE OF DRAWING 8 APR 66		GROMMET, RUBBER			
YP		TOLERANCES ON DECIMALS ±		DRAFTSMAN <i>WMB</i>	CHECKER <i>JP</i>				
TS		FRACTIONS ±		TRACER <i>WMB</i>	CHECKER <i>JP</i>				
EL 2	F11686528 RIFLE, M14 E2	ANGLES ± 1°		ENGINEER <i>N. J. Longoria</i>	ENGINEER <i>W. J. Longoria</i>				
RA	SEE ENGINEERING RECORDS	MATERIAL SEE NOTE 1		SUBMITTED <i>R. S. Henry</i>					
BH	NEXT ASSY USED ON APPLICATION	HEAT TREATMENT		APPROVED <i>R. S. Henry</i>		DWG SIZE B		CODE IDENT NO. 19205	
RH	APPLY PART NO.	FINAL PROTECTIVE FINISH				SCALE 4 / 1		UNIT WT SHEET 1 OF 1	
SWESP FORM NO. 1176-1 20 MAR 64 REV.									