

B 7790130

REVISIONS			
SYM	DESCRIPTION	DATE	APPROVAL
A1	REF EO NO. SA 24560	19 JAN 58	<i>R. H. Hearn</i>
B3	SEE EO NO. SA 25877	13 NOV 61	<i>R. H. Hearn</i>
C	SEE ERR HQR 30617	22 JAN 73	<i>R. H. Hearn</i>
D	SEE ERR HQR 50667	25 JUN 73	<i>R. H. Hearn</i>

SPRING - 7790131

 $\frac{3}{8}$ DATUM

LOAD, SEE NOTE 2 (B)

SHOE - 7790132

NOTES

1. THE SUPPLEMENTARY FINISH (MIL-W-3688) OF ALL COMPONENTS SHALL BE COMPLETELY DRY FOR A MINIMUM OF 20 MINUTES PRIOR TO ASSEMBLY.

(B) 2. THE LOAD REQUIRED TO STRIP ONE END CARTRIDGE FROM A FULLY LOADED CLIP SHALL NOT BE LESS THAN 1.8 POUNDS OR GREATER THAN 4.7 POUNDS.

(C) 3. MIL-C-45404 APPLIES.

CODE IDENT NO. 19204 (A)

PART NO. 7790130

FOR LIST OF PARTS, SEE ENGR PARTS LIST 7790130 (B) (D)

RIFLE, M21		PHYSICAL PROPERTIES	UNLESS OTHERWISE SPECIFIED		ORIGINAL DATE OF DRAWING	DEPT OF THE ARMY	
A12002927 RIFLE, M14		YP	DIMENSIONS ARE IN INCHES		15 JAN 58	U.S. ARMY WEAPONS COMMAND	
M14NM		TS	TOLERANCES ON FRACTIONS DECIMALS ANGLES		DRAFTSMAN <i>W. H. Hearn</i> CHECKER <i>S. S. C.</i>	ROCK ISLAND, ILL. 61201	
M14A1, M14(M)		EL2	± ± ±		TRACER <i>W. H. Hearn</i> CHECKER <i>S. S. C.</i>	DWO SIZE	
NEXT ASSY		RA	MATERIAL		ENGR <i>W. H. Hearn</i> ENGR <i>S. S. C.</i>	B 7790130	
USED WITH		BH	HEAT TREATMENT		SUBMITTER <i>W. H. Hearn</i> ORG CORPS	SHEET 1 OF 1	
APPLICATION		RH	FINAL PROTECTIVE FINISH		APPROVED BY ORDER OF THE CHIEF OF ORDNANCE <i>H. J. Lough</i> ORG CORPS	SCALE 4/1 UNIT WT. .018 LB	
DO NOT APPLY PART NO. AS SPECIFIED			SEE NOTE 1				

CLIP, CARTRIDGE,
7.62-MM,
5 ROUND