

NOTES:-

- 1-SPEC MIL-W-13855 AND ANSI Y14.5-1973 APPLY.
 - 2-UPSET BOSS AT ASSEMBLY TO SECURE SAFETY SPRING.
- NOTE, SAFETY SPRING MUST BE FREE TO ROTATE ABOUT BOSS AFTER STAKING.

REVISIONS			
SYM	DESCRIPTION	DATE	APPROVAL
XO			
-	PRODUCTION RELEASE ERR W2S2025	840420	JS
A	NORW4S2051/ 84 08 24 (ECPW5S2069 /85 12 23)	86 01 21	JS
B	ERR 2921248E (ECP G9S3062/890718)	900318	JS

HOUSING, HAMMER SPRING-8448292

PIN-7791367

SPRING-7267080

GUARD-7790990

NOTE 2

HAMMER-8448293

SPRING, HELICAL, COMPRESSION - 6008887

PLUNGER, HAMMER SPRING-8448692

PIN-5013668

HOUSING ASSEMBLY, TRIGGER-8448290

SAFETY-5546015

FIRING

TRIGGER ASSEMBLY - 5546026

SAFE

RECOIL

SEE SEPARATE PARTS LIST 9354354

PART NO. 9354354

MECHANICAL PROPERTIES YP TS EL2 RA BR RH		DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON DECIMALS ±.01 FRACTIONS ± 1/64 ANGLES ± 1°		ORIGINAL DATE OF DRAWING 82-06-01		U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER DOVER, NEW JERSEY 07801	
				DRAFTSMAN A.L.S.		CHECKED ENGR W.B.	
9386973 9386974 RIFLE M14NM		APPLICATION USED ON		S. ARIAS E. J. BRENNEN		FIRM NO. 19200	
SCALE 2/1		UNIT WT		SHEET		9354354	

SCANNED DUPLICATE ORIGINAL